



PERLUBE WL-68-D

PRODUCT DATA SHEET



Perlube WL-68-D is an outstanding, multipurpose lubricating and machine tool slideway oil. Perlube WL-68-D is a superior lubricating oil with excellent oxidation and corrosion protection as well as unsurpassed water separation characteristics.

Perlube WL-68-D load carrying and staying properties make it an excellent way lubricant.

TYPICAL SPECIFICATIONS

TEST	RESULT
Viscosity @ 100°F	317 - 389 S.U.S.
Flash Point, C.O.C.	320°F
ASTM, Color	6 - 8

PERFORMANCE DATA

- ◆ **RUST & CORROSION**
Copper Corrosion (D-130)
3 Hours @ 100°C: 1b
3 Hours @ 121°C: 2c
- ◆ **DEMULSIBILITY**
(D-2711)
Total Water Out: 85
Emulsion, ml: 0
- ◆ **FOUR BALL WEAR TEST**
(D-2266)
(20kg, 1 hr, 54°F, 1800 rpm)
Scar Diameter, mm: 0.30
- ◆ **FRICTIONAL TEST**
Cincinnati Milacron
Stick Slip Test: Pass
- ◆ **BIJUR FILTERABILITY**
Pass
- ◆ **OXIDATION AND THERMAL STABILITY**
High Temperature Test
(Modified D-2893)
(121°C @ 312 Hours, 10 Liter Air/Hr.)
% Viscosity Increase: 3.4
Precipitation Number: Trace

67280092002

This information is presented in good faith, but no warranty, express or implied is given. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. This is an uncontrolled copy and changes can be made to this document without notice.



PERKINS PRODUCTS, INC.

Manufacturer of Industrial Lubricants

7025 West 66th Place, Bedford Park, IL 60638

Phone: 708-458-2000 Fax: 708-458-2057 Watts: 800-342-6722

www.perkinsproducts.com

Quality
With
Integrity